



Simple answers to complex questions

Respironics NM3 Respiratory Profile Monitor

Mechanically ventilated patients are constantly challenging clinicians with complex questions regarding their current respiratory status and the adequacy of ventilatory support. The Respironics NM3 monitors physiologic gas exchange, deadspace, and alveolar tidal volume, as well as a host of accessory parameters. This valuable insight helps you answer the toughest clinical questions, throughout the continuum of care.

Key advantages

- True mainstream or sidestream CO₂ monitoring for intubated and non-intubated patients
- Portable and adaptable monitoring, on and off all conventional ventilators
- Direct interface with the V200 Ventilator to expand data collection and display

PHILIPS

Respironics NM3 highlights

The Respironics NM3 non-invasively monitors volumetric (VCO_2) and end-tidal ($EtCO_2$) capnography. Clinicians can use this information to minimize the duration of mechanical ventilation and optimize the potential for successful extubation when managing critically ill patients. At every stage of care, the NM3 monitors the patient's response to ventilation. Bright, sharp, and well organized display screens present physiologic information on the patient's readiness for less support and spontaneous breathing trials (VCO_2 , $MValv$, Vd/Vt). The lightweight, portable design allows inter-departmental use on ventilated patients and those under deep and conscious sedation.

Key applications

- Confirm proper endotracheal tube placement
- Determine true alveolar tidal volume, independent of dead space
- Determine the effects of ventilator changes before the first ABG is drawn
- Monitor appropriate PEEP levels, alveolar recruitment, and pulmonary perfusion
- Obtain non-invasive cardiac output measurements
- Assess readiness for weaning and extubation
- Monitor patients post-extubation and under conscious sedation



Monitor appropriate PEEP levels, alveolar recruitment, and pulmonary perfusion



Assess readiness for weaning and extubation

Specifications

Patient Types	
Adult, pediatric, and neonatal	
Operation	
Mainstream CO ₂	Capnostat 5 Sensor
Sidestream CO ₂	LoFlo Sensor (option)
Cardiac output	NICO Sensor (option)
Pulse oximetry	Masimo Sensors
Alerts	
Adjustable	ETCO ₂ , SpO ₂ , RR, no respiration, VCO ₂ , pulse rate, cardiac output
Audio (adjustable volume)	2 min, silence, or OFF
Visual	Screen indicator and alert bar with alarm priority
Nurse call	Normally opened, normally closed
Internal battery	
Life	45 min
Recharge time	12 h
Type	Lead acid gel cell
Communications	
Philips VueLink open interface	
Spacelabs Flexport open interface	
V200 interface	
Respi-Link	
Printer capability (PCL3 and PCL5)	
RS232	
USB	
Analog output port	

Parameters measured	Abbreviation
CO ₂ elimination	VCO ₂
End tidal carbon dioxide	ETCO ₂
Inspired carbon dioxide	Insp CO ₂
Mixed expired CO ₂	PeCO ₂
Respiration rate	RR
Oxygen saturation	SpO ₂
Pulse rate	♥
Positive end expiratory pressure	PEEP
Mean airway pressure	MAP
Peak inspiratory pressure	PIP
Peak expiratory pressure	PEP
Peak inspiratory flow	PIF
Peak expiratory flow	PEF
Systematic vascular resistance	SVR
Airway deadspace	Vd Aw
Deadspace to tidal volume ratio	Vd/Vt
Rapid shallow breathing index	RSBI
Minute volume	MV
Alveolar minute volume	MValv
Inspired tidal volume	Vti
Expired tidal volume	Vte
Dynamic compliance	Cdyn
Airway resistance	Raw
Cardiac output (option)	
Cardiac output	C.O.
Cardiac index	CI
Stroke volume	SV
Stroke volume index	SVI
Pulmonary capillary blood flow	PCBF



Monitoring post-extubation and during conscious sedation

Bright, color display

Visual alarm indicator



Easy to navigate controls

Front panel connections for all sensor inputs



LoFlo Sensor

for sidestream capnography



Capnostat 5 Sensor

for combined mainstream capnography and flow monitoring



Masimo SET® Rainbow

for SpO₂ monitoring of all patients

Please visit www.philips.com/NM3



© 2009 Koninklijke Philips Electronics N.V.
All rights are reserved. Capnostat, LoFlo, NICO, NM3, Respirationics, and V200 are trademarks of Respirationics, Inc. and its affiliates.

Philips Healthcare reserves the right to make changes in specifications and/or to discontinue any product at any time without notice or obligation and will not be liable for any consequences resulting from the use of this publication.

Philips Healthcare is part of Royal Philips Electronics

www.philips.com/healthcare
healthcare@philips.com
fax: +31 40 27 64 887

Printed in the U.S.A.
4522 962 55271 * SEP 2009

Philips Healthcare
Global Information Center
P.O. Box 1286
5602 BG Eindhoven
The Netherlands

Teleflex

Proudly Distributed by **Teleflex Medical**

Teleflex Medical Australia Pty Ltd
Level 4 Building B · 201 Coward Street
Mascot 2020 NSW · Australia
Ph: 1300 360 226 · austCS@teleflex.com
www.teleflexmedical.com.au

Teleflex Medical New Zealand
12 Victoria Street
Lower Hutt 50103 · New Zealand
Ph: 0800 601 100 · nzsupport@teleflex.com
www.teleflexmedical.co.nz